

EURISG

European Industrial Sizing Group

EURISG Sizing Case Report

ESR_103

Stand: **20/11/2019**

Dimensioning of ATEX explosion zones in the vicinity of relief pipe outlets

Vertraulichkeit | Nutzung | Haftung

Dieses Dokument ist erstellt und Eigentum der CSE-Engineering Center of Safety Excellence GmbH. Es ist vertraulich zu behandeln und darf nicht ohne schriftliche Genehmigung der CSE-Engineering und dem Einverständnis der Teilnehmer der EURISG Gruppe an Dritte weitergegeben werden. Dies gilt für die elektronische Weitergabe ebenso wie für eine Kopie des Dokuments. Die Ergebnisse des Dokumentes dürfen ohne schriftliche Genehmigung weder zitiert noch vervielfältigt werden. Jede Haftung für die Vollständigkeit und Richtigkeit des Dokuments wird ausgeschlossen. Es gelten die Compliance Richtlinien der EURISG-Gruppe.

CSE-Engineering Center of Safety Excellence GmbH | Joseph-von-Fraunhofer Str. 9 | D-76327 PFINZTAL

Revisions

File name	Modifications	Date
191120_ESR_103_Dimensioning of explosion zones in the vicinity of relief pipe outlets	First version CSE-Engineering	20.11.2019

Table of contents

Revisions.....	2
Table of contents.....	3
1 Introduction.....	4
2 Rules and Regulations.....	4
3 Determination of the extent of ATEX explosion zones.....	5
3.1 Calculation model according to DVGW G 442.....	5
3.2 Calculation model according to Schatzmann.....	7
3.2.1 Supercritical flow at the free jet inlet	8
3.3 Further investigations on the dimensions of explosive zones	9
4 Bibliography.....	11

1 Introduction

A key concept for explosion protection concepts is the definition of three hazard zones, where specific measures must be complied with. The determination of the size and shape of these zones in the vicinity of relief pipe outlets e.g. from safety valves or rupture disks is the subject of this report.

2 Rules and Regulations

The requirements for operational explosion protection are demanded by the EU directive 2014/34/EU [1] and 1999/92/EG [2] which are regulated for Germany in the "Gefahrstoffverordnung" (GefStoffV) [3] and the "Betriebssicherheitsverordnung" (BetrSichV) [4]. Based on a risk assessment the employer has to ensure the safety of his employees. The risk assessment as a base for an explosion protection document is demanded by several regulations: Arbeitsschutzgesetz [5], GefStoffV, BetrSichV, BGV A1 [6]. The "GefStoffV" defines ATEX hazard zones for explosion protection as follows:

Zone 0

is a place in which a potentially explosive atmosphere consisting of a mixture of air and flammable substances in the form of gas, vapour or mist is present continuously, for long periods or frequently.

Zone 1

is a place in which an explosive atmosphere consisting of a mixture of air and flammable substances in the form of gas, vapour or mist may occasionally occur in normal operation.

Zone 2

is a place in which, during normal operation, a dangerous explosive atmosphere consisting of a mixture of air and flammable substances in the form of gas, vapour or mist is not likely to occur and, if it does occur, only rarely and for a short period of time.

Regarding the size and dimensions of hazard zones in the vicinity of relief pipe outlets to the environments the following regulatory passages and guidance is available.

As guidance the "Deutsche Gesetzliche Unfallversicherung" (DGUV); department "Rohstoffe und chemische Industrie", subject area "Explosionsschutz" developed the document "DGUV Regel 113-001 – Explosionsschutz-Regeln (EX-RL)" [7]. This document is a collection of technical rules specifying the "GefStoffV" and the "BetrSichV". To determine the ATEX hazard zones in the vicinity of relief pipes, this rule refers to the "DVGW-Hinweis G 442".